

ZC - Series

DriveRack Series Wall-Mounted Zone Controllers

dbx®
PROFESSIONAL PRODUCTS



ZC-1



ZC-2



ZC-3



ZC-4



ZC-BOB

VISIONARY DESIGN

The Zone Controllers offer extended utility to the DriveRack™ family. Based on the same unparalleled design philosophy as the other products in the dbx® line-up, the Zone Controllers offer additional control to installations featuring the DriveRack™ 260. The five Zone Controllers use analog DC voltages to provide logic control ranging from Volume and Mute control, to Contact Closure Program selection. Wired with readily available and affordable CAT5 cable with universally accepted RJ-45 connectors, the ZC Zone Controllers offer simple yet elegant solutions to the contractor.

REVOLUTIONARY ENGINEERING

The ZC-1 offers remote programmable, Volume control to any installation using the DriveRack™ 260. The ZC-2 provides programmable Volume and Mute control. Both the ZC-1 and ZC-2 can be programmed for up to six outputs of the DriveRack™ 260. The ZC-3 allows Program Selection on the 260. The ZC-4 also offers Program Selection via Contact Closure inputs for Room Combining applications. Up to six Zone Controllers can be used with a single DriveRack™ 260, and can either be wired in series or parallel. The ZC-BOB was created to accommodate "home-run" or parallel wiring to the unit. With a maximum recommended cable length of 1,000 feet, the Zone Controllers offer a simple way to create elegant solutions for many installation applications. For more information please visit www.driverack.com or www.dbxpro.com.

FEATURES

- **Programmable Volume Control**
- **Programmable Volume and Mute Control**
- **Program Selection**
- **Contact Closure Program Selection**
- **Maximum recommended cable length of 1,000 ft.**
- **Series or "Home Run" cabling**
- **Readily available CAT5 cable**
- **Standard RJ-45 Connectors**

8760 S. Sandy Pkwy.
Sandy, Utah 84070
Phone (801) 568-7660
Fax (801) 568-7662
Int'l Fax (801) 568-7583
customer@dbxpro.com
<http://www.dbxpro.com>

H A Harman International Company

18-0180-B 1/03

ZC-Series

DriveRack™ Series Wall-Mounted Zone Controllers



ZC-1



ZC-2



ZC-3



ZC-4



ZC-BOB

SPECIFICATIONS

Connections:

ZC-1, ZC-2, ZC-3 Connectors: (2) RJ-45

ZC-4 Connectors: (2) RJ-45, (1) 6-pin Phoenix

ZC-BOB Connectors: (7) RJ-45

Wiring:

Maximum Cable Length depends on number of Zone Controllers and wiring schematic.

Series Wiring:

Maximum Cable Length varies with number of Zone Controllers.

For Example, Three Zone Controllers: 600 ft.

Six Zone Controllers:

300 ft. Parallel Wiring using a ZC-BOB:

Up to Six Zone Controllers: 1000 ft.

Cable:

CAT5 or CAT5E with 28.6 Ohm/M (Ohm/1000 ft.) nominal DCR and rated VW-1 or higher.

Safety Agency Approvals:

UL 6500, IEC 60065, EN 55013, E60065

dbx engineers are constantly working to improve the quality of our products. Specifications are, therefore subject to change without notice.

FOR MORE INFORMATION CONTACT:

dbx Professional Products

8760 S. Sandy Pkwy.

Sandy, Utah 84070

Phone (801) 568-7660

Fax (801) 568-7662

customer@dbxpro.com

<http://www.dbxpro.com>



The Professional's Choice In Signal Processing™

H A Harman International Company